

Text::Table

example: center align and Unicode output

```
#!/usr/bin/perl

use strict;
use warnings;
use utf8;

use Text::Table ();

binmode STDOUT, ':encoding(utf8)';

my @cols = qw/First Last/;
push @cols,
    +{
        title => "Country",
        align => "center",
    };
my $sep = \'|';

my $major_sep = \'|';
my $tb      = Text::Table->new( $sep, " Number ", $major_sep,
    ( map { +( ( ref($_) ? $_ : " $_ " ), $sep ) } @cols ) );

my $num_cols = @cols;

$tb->load( [ 1, "Mark",      "Twain",      "USA", ] );
$tb->load( [ 2, "Charles",  "Dickens", "Great Britain", ] );
$tb->load( [ 3, "Jules",    "Verne",   "France", ] );

my $make_rule = sub {
    my ($args) = @_;

    my $left      = $args->{left};
    my $right     = $args->{right};
    my $main_left = $args->{main_left};
    my $middle    = $args->{middle};

    return $tb->rule(
        sub {
            my ( $index, $len ) = @_;

            return ( '-' x $len );
        },
        sub {
            my ( $index, $len ) = @_;
```

```

    my $char = (
        ( $index == 0 )           ? $left
        : ( $index == 1 )       ? $main_left
        : ( $index == $num_cols + 1 ) ? $right
        :                         $middle
    );

    return $char x $len;
},
);
};

my $start_rule = $make_rule->(
{
    left      => '┌',
    main_left => '├',
    right     => '┐',
    middle    => '┤',
}
);

my $mid_rule = $make_rule->(
{
    left      => '┆',
    main_left => '┆',
    right     => '┆',
    middle    => '┆',
}
);

my $end_rule = $make_rule->(
{
    left      => '└',
    main_left => '┘',
    right     => '┘',
    middle    => '┘',
}
);

print $start_rule, $tb->title,
      ( map { $mid_rule, $_, } $tb->body() ), $end_rule;

```

This emits the following output:

Number	First	Last	Country
1	Mark	Twain	USA
2	Charles	Dickens	Great Britain

3	Jules	Verne	France	
---	-------	-------	--------	--